

Deterministic Cold-Temperature Altimetry Corrections: Mathematical Derivations of ICAO Doc 8168 Hypsometric Models vs. FAA AIM Table Heuristics and Surface Inversions

Miad S.¹

¹Lead System Architect & Aeronautical Computing Specialist, Aeroway Aeronautical Research Group, Aeroway Flight Engineering (aeroway.org)

Abstract— Barometric altimeters compute indicated altitude under standard atmospheric assumptions (ICAO Doc 7488/3). Under sub-zero conditions where the air column is colder than standard ($T(z) < T_{ISA}(z)$), air density increases, causing vertical isobaric surfaces to contract toward the ground. An altimeter referencing this contracted air column registers an indicated altitude higher than true physical altitude ($z_{true} < z_{ind}$), systematically reducing obstacle clearance. This monograph derives the hypsometric altimetry error integral from the hydrostatic equation and ideal gas law. We evaluate three operational frameworks across a 5,425-vector computational benchmark matrix: (1) the continuous ICAO Doc 8168 (PANS-OPS) Vol II layer formulation, (2) the discrete FAA AIM Table 7-3-1 lookup grid, and (3) the flight-training 4 ft/°C/1,000 ft linear rule. We prove the Taylor-series basis of the linear rule, quantify its under-correction at severe sub-zero temperatures (105.1 ft divergence at −40°C across 5,000 ft HAA), model synthetic boundary-layer surface inversions, and analyze Baro-VNAV glidepath compression (where a 3.00° indicated path compresses to 2.42° true under −40°C ISA deviation).

1. Fundamental Thermodynamics & The Hydrostatic Equation

A static atmospheric column in hydrostatic equilibrium balances gravitational attraction with vertical pressure gradient force: $dp/dz = -\rho(z) \cdot g$. Applying the Ideal Gas Law for dry air ($p = \rho R_d T$, with $R_d = 287.05287 \text{ J/(kg}\cdot\text{K)}$) yields the differential barometric relationship: $dp/p = -[g / (R_d T(z))] dz$.

2. The Generalized Hypsometric Integral & Height Ratio

Integrating between reference station pressure datum p_{ref} and flight pressure p establishes the fundamental ratio between true geometric height displacement (H_{true}) and standard indicated displacement (H_{ind}):

$$H_{true} = H_{ind} \cdot \left[T_{actual} / T_{ISA} \right] \quad | \quad \Delta h_{corr} = H_{true} \cdot \left[-\Delta T / T_{actual} \right]$$

3. ICAO Doc 8168 Analytical Layer Formulation

ICAO Doc 8168 (PANS-OPS) Volume I Part VI § 1.4.1 & Volume II establishes the operational layer correction equation: $\Delta h = H \cdot \left[(15 - t) / (273.15 + t - 0.5 \cdot L \cdot (H + H_{ss})) \right]$, where $t = t_{aerodrome} + L \cdot H_{ss}$ is aerodrome temperature reduced to sea level at standard lapse rate ($L = 0.0019812 \text{ }^\circ\text{C/ft}$).

4. Quantitative Model Divergence (5,425-Vector Benchmark Matrix)

Evaluating DATASET-2026-02 across 5 elevations, 31 temperatures, and 35 HAA levels at sea level datum ($H_{ss} = 0 \text{ ft}$):

Surface Temp	HAA (H)	ICAO Layer Model	FAA Table 7-3-1	Linear 4% Rule	Model vs. Linear	Model vs. Table
0°C	1,000 ft	55.1 ft	60 ft	60.0 ft	−4.9 ft	−4.9 ft
0°C	5,000 ft	279.6 ft	290 ft	300.0 ft	−20.4 ft	−10.4 ft
−20°C	3,000 ft	419.7 ft	430 ft	420.0 ft	−0.3 ft	−10.3 ft
−20°C	5,000 ft	705.1 ft	710 ft	700.0 ft	+5.1 ft	−4.9 ft
−40°C	4,000 ft	959.9 ft	970 ft	880.0 ft	+79.9 ft	−10.1 ft
−40°C	5,000 ft	1,205.1 ft	1,210 ft	1,100.0 ft	+105.1 ft	−4.9 ft

−50°C	5,000 ft	1,489.5 ft	1,500 ft	1,300.0 ft	+189.5 ft	−10.5 ft
-------	----------	------------	----------	------------	-----------	----------

5. Synthetic Inversions & Baro-VNAV Glidepath Compression

Surface Inversions: Under a synthetic surface radiative inversion (−35°C warming at +8.33°C/1,000 ft to −10°C at 3,000 ft AGL), the physical average column temperature is 250.6 K versus the 235.2 K assumed by surface-extrapolated linear models. Surface-based calculations overestimate corrections by 60 to 110 ft in strong inversions.

Baro-VNAV Compression: The true vertical descent angle compresses according to $\gamma_{true} = \arctan[(T_{actual} / T_{ISA}) \cdot \tan(\gamma_{ind})]$. At −40°C across 5,000 ft HAA, a nominal 3.00° indicated glidepath flattens to **2.42° true**, reducing intermediate fix obstacle clearance margins.

6. References & Open Data Availability

1. ICAO (1993). *Manual of the ICAO Standard Atmosphere*, Doc 7488/3.

2. ICAO (2018). *PANS-OPS: Flight Procedures*, Doc 8168 Vol I & Vol II.

3. FAA (2026). *Aeronautical Information Manual (AIM)*, Chapter 7 Section 3 (7-3-1 to 7-3-5).

4. Transport Canada (2024). *Canadian Aviation Regulations*, CAR 602.127 & AIM RAC § 9.17.

5. EASA (2022). *Easy Access Rules for Air Operations*, GM8 CAT.OP.MPA.110.

6. Benchmark Dataset: Miad S. (2026). *Cold-Temperature Altimetry Benchmark (5,425 Modeled Vectors)*. Aeroway Open Data Archive (DATASET-2026-02).